Wireless Communications Standards



DIGITAL CELLULAR STANDARDS

5G NR

Frequency range

3GPP Release 15:
FR 1: 0.45 GHz to 6 GHz
FR 2: 24.25 GHz to 52.6 GHz

Sub-6 GHz Bands (in MHz)
1) FDD UL: 1920 to 1980 DL: 2110 to 2170
2) FDD UL: 1850 to 1910 DL: 1930 to 1990
3) FDD UL: 1710 to 1785 DL: 1805 to 1880
5) FDD UL: 824 to 849 DL: 869 to 894
7) FDD UL: 2500 to 2570 DL: 2620 to 2690
8) FDD UL: 880 to 915 DL: 925 to 960
20) FDD UL: 832 to 862 DL: 791 to 821
28) FDD UL: 703 to 748 DL: 758 to 803
38) FDD UL: 2570 to 2620
41) TDD UL: DL: 2496 to 2690
50) TDD UL: 1432 to 1517
51) TDD UL: DL: 1427 to 1432
66) FDD UL: 1710 to 1780 DL: 2110 to 2200
70) FDD UL: 1695 to 1710 DL: 1995 to 2020
71) FDD UL: 663 to 698 DL: 617 to 652
74) FDD UL: 1427 to 1470 DL: 1475 to 1518
75) SDL UL: - DL: 1432 to 1517
76) SDL UL: - DL: 1427 to 1432
77) TDD UL: DL: 3300 to 4200
78) TDD UL: DL: 3300 to 3800
79) TDD UL: DL: 4400 to 5000
80) SUL UL: 1710 to 1785 DL: -
81) SUL UL: 880 to 915 DL: -
82) SUL UL: 832 to 862 DL: -
83) SUL UL: 703 to 748 DL: -
84) SUL UL: 1920 to 1980 DL: -

mmWave Bands (in GHz)
257) TDD UL: DL: 26.5 to 29.5
258) TDD UL: DL: 24.25 to 27.5
260) TDD UL: DL: 37 to 40

LTE/LTE-Advanced/ LTE-Advanced Pro

E-UTRA FDD and TDD Bands (in MHz)
1) FDD UL: 1920 to 1980 DL: 2110 to 2170 (LTE-M, NB-IoT)
2) FDD UL: 1850 to 1910 DL: 1930 to 1990 (LTE-M, NB-IoT)
3) FDD UL: 1710 to 1785 DL: 1805 to 1880 (LTE-M, NB-IoT)
4) FDD UL: 1710 to 1755 DL: 2110 to 2155 (LTE-M)
5) FDD UL: 824 to 849 DL: 869 to 894 (LTE-M, NB-IoT)
6) FDD UL: 830 to 840 DL: 875 to 885
7) FDD UL: 2500 to 2570 DL: 2620 to 2690 (LTE-M)
8) FDD UL: 880 to 915 DL: 925 to 960 (LTE-M, NB-IoT)
9) FDD UL: 1749.9 to 1784.9 DL: 1844.9 to 1879.9
10) FDD UL: 1710 to 1770 DL: 2110 to 2170
11) FDD UL: 1427.9 to 1447.9 DL: 1475.9 to 1495.9
12) FDD UL: 699 to 716 DL: 729 to 746
13) FDD UL: 777 to 787 DL: 746 to 756
14) FDD UL: 788 to 798 DL: 758 to 768
15) FDD UL: 1900 to 1920 DL: 2585 to 2600 (Europe only)
16) FDD UL: 2010 to 2025 DL: 2585 to 2600 (Europe only)
17) FDD UL: 704 to 716 DL: 734 to 746 (NB-IoT)
18) FDD UL: 815 to 830 DL: 860 to 875 (LTE-M, NB-IoT)
19) FDD UL: 830 to 845 DL: 875 to 890 (LTE-M, NB-IoT)
20) FDD UL: 832 to 862 DL: 791 to 821
21) FDD UL: 1447.9 to 1462.9 DL: 1495.9 to 1510.9 (LTE-M)
22) FDD UL: 3410 to 3490 DL: 3510 to 3590
23) FDD UL: 2000 to 2020 DL: 2180 to 2200
24) FDD UL: 1626.5 to 1660.5 DL: 1525 to 1559
25) FDD UL: 1850 to 1915 DL: 1930 to 1995 (LTE-M, NB-IoT)
26) FDD UL: 814 to 849 DL: 859 to 894 (LTE-M, NB-IoT)
27) FDD UL: 807 to 824 DL: 852 to 869 (LTE-M)
28) FDD UL: 703 to 748 DL: 758 to 803 (LTE-M, NB-IoT)
29) FDD UL: - DL: 717 to 728
30) FDD UL: 2305 to 2315 DL: 2360 to 2360
31) FDD UL: 452.5 to 457.5 DL: 462.5 to 467.5 (LTE-M, NB-IoT)
32) FDD UL: - DL: 1452 to 1496
33) TDD UL, DL: 1900 to 1920
34) TDD UL, DL: 2010 to 2025
35) TDD UL: 1850 to 1910
36) TDD UL: 1930 to 1990
37) TDD UL: 1910 to 1930
38) TDD UL, DL: 2570 to 2620
39) TDD UL: 1880 to 1920 (LTE-M)
40) TDD UL, DL: 2300 to 2400 (LTE-M)
41) TDD UL: 2496 to 2690 (LTE-M)
42) TDD UL, DL: 3400 to 3600
43) TDD UL, DL: 3600 to 3800
44) TDD UL, DL: 703 to 803
45) TDD UL, DL: 1447 to 1467
46) TDD UL, DL: 5150 to 5925
47) TDD UL, DL: 5855 to 5925
48) TDD UL, DL: 3550 to 3700
50) TDD UL, DL: 1432 to 1517
51) TDD UL: 1427 to 1432
65) FDD UL: 1920 to 2010
DL: 2110 to 2200
66) FDD UL: 1710 to 1780
DL: 2110 to 2200 (NB-IoT)
67) FDD UL: - DL: 738 to 758
68) FDD UL: 698 to 728 DL: 753 to 783
69) FDD UL: - DL: 2570 to 2620
70) FDD UL: 1695 to 1710
DL: 1995 to 2020 (NB-IoT)
71) FDD UL: 663 to 698 DL: 617 to 652
72) FDD UL: 451 to 456 DL: 461 to 466
74) FDD UL: 1427 to 1470
DL: 1475 to 1518
75) FDD UL: - DL: 1432 to 1517
76) FDD UL: - DL: 1427 to 1432

LTE-M

NB-IoT

LTE D2D

Bands (in MHz)
E-UTRA Bands
2) UL, DL: 1850 to 1910
3) UL, DL: 1710 to 1785
4) UL, DL: 1710 to 1755
5) UL, DL: 824 to 849
7) UL, DL: 2500 to 2570
13) UL, DL: 777 to 787
14) UL, DL: 788 to 798
20) UL, DL: 814 to 849
28) UL, DL: 703 to 748
41) UL, DL: 2496 to 2690
68) UL, DL: 698 to 728
72) UL, DL: 451 to 456

WCDMA/HSPA/HSPA+

UTRA FDD Bands (in MHz)
1) UL: 1920 to 1980 DL: 2110 to 2170
2) UL: 1850 to 1910 DL: 1930 to 1990
3) UL: 1710 to 1785 DL: 1805 to 1880
4) UL: 1710 to 1755 DL: 2110 to 2155
5) UL: 824 to 849 DL: 869 to 894
6) UL: 830 to 840 DL: 875 to 885
7) UL: 2500 to 2570 DL: 2620 to 2690
8) UL: 880 to 915 DL: 925 to 960
9) UL: 1749.9 to 1784.9 DL: 1844.9 to 1879.9
10) UL: 1710 to 1770 DL: 2110 to 2170
11) UL: 1427.9 to 1447.9 DL: 1475.9 to 1495.9
12) UL: 699 to 716 DL: 729 to 746
13) UL: 777 to 787 DL: 746 to 756
14) UL: 788 to 798 DL: 758 to 768
19) UL: 830 to 845 DL: 875 to 890
20) UL: 832 to 862 DL: 791 to 821
21) UL: 1447.9 to 1462.9 DL: 1495.9 to 1510.9
22) UL: 3410 to 3490 DL: 3510 to 3590
25) UL: 1850 to 1915 DL: 1930 to 1995
26) UL: 814 to 849 DL: 859 to 894
27) UL: – DL: 1452 to 1496

TD-SCDMA

UTRA Bands (in MHz)
33) 1900 to 1920
34) 2010 to 2025
35) 1850 to 1910
36) 1930 to 1990
37) 1910 to 1930
38) 2570 to 2620
39) 1880 to 1920
40) 2300 to 2400

GSM/GPRS/EDGE/ EDGE Evolution/VAMOS

Bands (in MHz)
T-GSM 380
UL: 380.2 to 389.8 DL: 390.2 to 399.8
T-GSM 410
UL: 410.2 to 419.8 DL: 420.2 to 429.8
GSM 450
UL: 450.4 to 457.6 DL: 460.4 to 467.6
GSM 480
UL: 478.8 to 486 DL: 488.8 to 496
GSM 710
UL: 698 to 716 DL: 728 to 746
GSM 750
UL: 777 to 793 DL: 747 to 763
T-GSM 810
UL: 806 to 821 DL: 851 to 866
GSM 850
UL: 824 to 849 DL: 869 to 894
P-GSM 900
UL: 890 to 915 DL: 935 to 960
E-GSM 900
UL: 880 to 915 DL: 925 to 960
R-GSM 900
UL: 876 to 915 DL: 921 to 960
DCS 1800
UL: 1710 to 1785 DL: 1805 to 1880
PCS 1900
UL: 1850 to 1910 DL: 1930 to 1990
ER-GSM 900
UL: 873 to 915 DL: 918 to 960

CDMA2000® 1xEV-DO Release 0/Revision A/ Revision B

Band Classes (in MHz)
BC0) RL: 815 to 849
BC1) RL: 1850 to 1910
BC2) RL: 872 to 915
BC3) RL: 887 to 925
BC4) RL: 1750 to 1780
BC5) RL: 410 to 483
BC6) RL: 1920 to 1980
BC7) RL: 776 to 788
BC8) RL: 1710 to 1785
BC9) RL: 880 to 915
BC10) RL: 806 to 901
BC11) RL: 410 to 483
BC12) RL: 870 to 876
BC13) RL: 2500 to 2570
BC14) RL: 1850 to 1915
BC15) RL: 1710 to 1755
BC16) RL: 2502 to 2568
BC17) RL: 2624 to 2690,
BC18) RL: 787 to 799
BC19) RL: 698 to 716
BC20) RL: 1626 to 1660
BC21) RL: 2000 to 2020

CDMA2000® 1xRTT/ 1xAdvanced

FL: 860 to 894
FL: 1930 to 1990
FL: 917 to 960
FL: 832 to 870
FL: 1840 to 1870
FL: 420 to 493
FL: 2110 to 2170
FL: 746 to 758
FL: 1805 to 1880
FL: 925 to 960
FL: 851 to 940
FL: 420 to 493
FL: 915 to 921
FL: 2620 to 2690
FL: 1930 to 1995
FL: 2110 to 2155
FL: 2624 to 2690
1xEV-DO only
FL: 757 to 769
FL: 728 to 746
FL: 1525 to 1559
FL: 2180 to 2200

WiMAX™/ WiMAX™ Advanced

IEEE 802.16-2012/ IEEE 802.16m

Profiles for WiMAX™ (in MHz)
M2300T-01/02
2300 to 2400
M2500T-01
2496 to 2690
M3500T-02/03/05
3400 to 3600

Targeted for WiMAX™ Advanced:
UTRA/TDD Bands
VHF: 136 to 174
UHF: 380 to 470
UHF: 450 to 512
700/800:
764 to 870

PUBLIC SAFETY STANDARDS

TETRA TETRA 2 (TEDS)

Bands (in MHz)
UL: 351 to 356
DL: 361 to 366
UL: 380 to 390
DL: 390 to 400
UL: 410 to 420
DL: 420 to 430
UL: 450 to 460
DL: 460 to 470
UL: 806 to 825
DL: 851 to 870

Tetrapol

Band (in MHz)
70 to 520

Project 25

APCO-25

Bands (in MHz)
RC1 (e.g. Europe):
868.0 to 868.6
RC2 (e.g. North America):
902 to 928
RC3 (e.g. Japan):
920.5 to 929.7
RC4 (e.g. Australia):
920.1375 to 922.6625
RC5:
920.8 to 923.4

LPWAN

SIGFOX

Bands (in MHz)
11b, g, n, ax:
2400 to 2497
11a, n, ac, ax:
5150 to 5250
5250 to 5350
(DFS required)
5470 to 5725
(DFS required)
5725 to 5850
11p:
5850 to 5925
11p, Japan:
755 to 765
Europe:
863 to 868
US:
902 to 928
Japan:
916.5 to 927.5
South Korea:
917.5 to 923.5
China:
755 to 787
Singapore:
866 to 869
920 to 925
11ad, ay:
Europe:
57 to 66
US:
57 to 71
South Korea:
57 to 64
Japan:
57 to 66
Australia:
55.4 to 62.9
China:
59 to 64
11aj China:
42.3 to 48.4
59 to 64

LoRaWAN

Bands (in MHz)
Europe:
863 to 870
433
North America:
902 to 928
China:
779 to 787
470 to 510
Australia:
915 to 928
Asia:
923
South Korea:
920 to 923
India:
865 to 867

WIRELESS CONNECTIVITY

WLAN/Wi-Fi IEEE 802.11a, b, g, n, p, ac, ax

Bands (in MHz)
11b, g, n, ax:
2400 to 2497
11a, n, ac, ax:
5150 to 5250
5250 to 5350
(DFS required)
5470 to 5725
(DFS required)
5725 to 5850
11p:
5850 to 5925
11p, Japan:
755 to 765

WLAN/Wi-Fi HaLow™ IEEE 802.11ah

Bands (in MHz)
Europe:
863 to 868
US:
902 to 928
Japan:
916.5 to 927.5
China:
755 to 787
Singapore:
866 to 869
920 to 925

WLAN/Wi-Fi IEEE 802.11ad, aj*, ay*

Bands (in MHz)
11ad, ay:
Europe:
57 to 66
US:
57 to 71
South Korea:
57 to 64
Japan:
57 to 66
Australia:
55.4 to 62.9
China:
59 to 64
11aj China:
42.3 to 48.4
59 to 64

Bluetooth®

Band (in MHz)
2400 to 2483.5

LR-WPAN ZigBee/Thread/ 6LoWPAN IEEE 802.15.4

Bands (in MHz)
169.4 to 169.475
250 to 750
779 to 787
863 to 879
896 to 960
1427 to 1518
2360 to 2483.5
3244 to 4742
5944 to 10234

ZigBee 3.0, Thread, 6LoWPAN:
2360 to 2483.5

NFC, RFID ISO/IEC 18000, NFC Analog Specification

125 kHz to 134 kHz
6.7 MHz
13.56 MHz **(NFC)**
27 MHz
433 MHz

Europe:
865 MHz to
868 MHz

North America:
902 MHz to
928 MHz

2.45 GHz
5.8 GHz
24.125 GHz

DECT, ULE

Bands (in MHz)
World:
1900 to 1920
1910 to 1930

Europe:
1880 to 1900

US:
1920 to 1930

GNSS

GPS USA (global)

L1-C/A, L1C, P(Y), M:
1575.42 MHz
L2, L2C:
1227.60 MHz
L5: 1176.45 MHz

Galileo EU (global)

E1:
1575.42 MHz
E5:
1191.795 MHz
E5a:
1176.45 MHz
E5b:
1207.14 MHz
E6:
1278.75 MHz

GLONASS Russia (global)

L1OF, L1SF (FDMA):
1602 MHz + n × 0.5625 MHz
L1OC, L1SC (CDMA):
1600.996 MHz
L2OF, L2SF (FDMA):
1246 MHz + n × 0.4375 MHz
L2OC, L2SC (CDMA):
1248.06 MHz
L3 (CDMA):
1202.025 MHz

BeiDou China (global)

B1:
1575.42 MHz
B2:
1191.79 MHz
B3:
1268.52 MHz

QZSS Japan (regional)

L1-C/A, L1C, L1-SAIF:
1575.42 MHz
L2C:
1227.60 MHz
L5:
1176.45 MHz
L6:
1278.75 MHz
S-band: 2 GHz band

IRNSS India (regional)

L5:
1176.45 MHz
S:
2492.028 MHz

	5G NR	LTE/LTE-Advanced/ LTE-Advanced Pro	LTE-M	NB-IoT	LTE D2D	WCDMA/HSPA/HSPA+	TD-SCDMA	GSM/GPRS/EDGE/ EDGE Evolution/VAMOS	CDMA2000® 1xEV-DO Release 0/Revision A/ Revision B	CDMA2000® 1xRTT/ 1xAdvanced	WiMAX™/ WiMAX™ Advanced IEEE 802.16-2012/ IEEE 802.16m
Modulation type	up to 256QAM (DL, UL)	QPSK, 16QAM, 64QAM, 256QAM (DL) QPSK, 16QAM, 64QAM, 256QAM in preparation (UL)	QPSK, 16QAM	BPSK, QPSK	QPSK (discovery) QPSK, 16QAM (communication)	QPSK (DL) 16QAM (DL, HSDPA) 64QAM (DL, HSPA+) Dual BPSK (UL) 16QAM, 64QAM (UL, HSPA+)	QPSK, 8PSK 16QAM (HSPA) 64QAM (HSPA+)	GMSK 8PSK (EDGE) QPSK, 16QAM, 32QAM (EDGE Evolution) AQPSK (VAMOS)	QPSK, 8PSK, 16QAM (FL) 64QAM (FL, Rev. B) 8PSK, QPSK, 8PSK (RL)	QPSK (FL) HPSK, OQPSK (RL)	8PSK, QPSK, 16QAM, 64QAM
Transmission method/ multiple access	CP-OFDM (DL); CP-OFDM, DFT-s-OFDM (UL)	OFDMA (DL) localized SC-FDMA (UL, LTE Rel. 8) localized and distributed SC-FDMA (UL, LTE Rel.10)	OFDMA (DL); localized SC-FDMA (UL, LTE Rel.8) localized and distributed SC-FDMA (UL, LTE Rel.10)	OFDMA (DL) SC-FDMA (UL)	SC-FDMA	WCDMA	TD-SCDMA, FDMA	TDMA, FDMA	TDMA (FL) CDMA (RL)	CDMA	OFDM (256) (16-2012 only) SOFDMA (128, 256, 512, 1024, 2048)
Duplex	Dynamic TDD; FDD	FDD, TDD	FDD, TDD	FDD	TDD	FDD	TDD	FDD	FDD	FDD	TDD, FDD/HFDD
Channel bandwidth	**Network operators:** 100 MHz per CC, max. 800 MHz (BC) **3GPP:** max. 100 MHz/CC (Sub-6 GHz) max. 400 MHz/CC (mmWave)	Scalable to 20 MHz LTE-A: up to 100 MHz (max. 5 carrier × 20 MHz) LTE-A Pro: up to 640 MHz (max. 32 carrier x 20 MHz) LTE M1: 1.4 MHz	Cat-M1: 1.4 MHz Cat-M2: 5.0 MHz	180 kHz	Scalable to 20 MHz LTE-A: up to 100 MHz (max. 5 carrier × 20 MHz)	5 MHz (WCDMA/HSPA) 10 MHz (HSPA+(DC-HSPA)) 20 MHz (HSPA+(four carrier HSDPA)) 40 MHz (HSPA+(eight carrier HSDPA))	1.6 MHz	200 kHz (GSM/EDGE) 400 kHz (EDGE Evolution)	1.25 MHz (Rel. 0/Rev. A) 1.25 MHz x N (Rev. B) (N = number of channels, max. 15)	1.25 MHz	16-2012: 5 MHz, 7 MHz, 8.75 MHz, 10 MHz 16m: 5 MHz to 20 MHz optionally 40 MHz
Peak data rate	>20 Gbit/s (DL)	300 Mbit/s (DL, Rel.8, 20 MHz, 4x4 MIMO, UE Cat.5) 75 Mbit/s (UL, Rel.8, 20 MHz, 64QAM, UE Cat.5) 3 Gbit/s (DL, LTE-A, 100 MHz, 8x8 MIMO, UE Cat.8) 1.5 Gbit/s (UL, LTE-A, 100 MHz, 4x4 MIMO, UE Cat.8) 25 Gbit/s (DL, LTE-A Pro, 100 MHz, 8x8 MIMO, UE Cat.17) 9.5 Gbit/s (UL, LTE-A Pro, 100 MHz, UE Cat.14) 1 Mbit/s (DL, UL, LTE M1)	1 Mbit/s (DL, UL, Cat-M1) 2 Mbit/s (DL, UL, Cat-M2)	250 kbit/s	11.6 Mbit/s (discovery) 25 Mbit/s (communication)	384 kbit/s (DL, UL) 14.4 Mbit/s (DL, HSDPA) 5.76 Mbit/s (UL, HSUPA) 28 Mbit/s (DL, HSPA+, 16QAM, MIMO) 84.4 Mbit/s (DL, HSPA+, 64QAM, MIMO, DC) 168 Mbit/s (DL, HSPA+, 64QAM, MIMO, 4C) 337 Mbit/s (DL, HSPA+, 64QAM, MIMO, 8C) 11.5 Mbit/s (UL, HSPA+, 16QAM) 23 Mbit/s (UL, HSPA+, 16QAM, DC) 34 Mbit/s (UL, HSPA+, 64QAM)	2.8 Mbit/s (DL, HSDPA) 2.2 Mbit/s (UL, HSUPA) 8.4 Mbit/s (DL, HSPA+) 2.2 Mbit/s (UL, HSPA+)	14.4 kbit/s (GSM) 171.2 kbit/s (DL, 8 slots, GPRS) 128.4 kbit/s (UL, 6 slots, GPRS) 473.6 kbit/s (DL, 8 slots, EDGE) 355.2 kbit/s (UL, 6 slots, EDGE) 1.89 Mbit/s (DL, 8 slots, EGPRS2-B and DL DC) 710 kbit/s (UL, 6 slots, EGPRS2-B)	2.4 Mbit/s (FL, Rel. 0) 153 kbit/s (RL, Rel. 0) 3.1 Mbit/s (FL, Rev. A) 1.8 Mbit/s (RL, Rev. A) 4.9 Mbit/s x N (FL, Rev. B) 1.8 Mbit/s x N (RL, Rev. B) (N = number of channels, max. 15)	153.6 kbit/s (Rel. 0) 307.7 kbit/s (Rev. E)	16-2012: 128 Mbit/s (DL, 20 MHz, 2x2 MIMO) 56 Mbit/s (UL, 20 MHz, 2x2 MIMO) 16m: 300 Mbit/s (DL, 20 MHz, 4x4 MIMO) 135 Mbit/s (UL, 20 MHz, 2x4 MIMO)
Standardization forums	www.3gpp.org	www.3gpp.org www.globalcertificationforum.org www.ptcrb.com							www.3gpp2.org www.globalcct.org		www.ieee802.org/16 www.wimaxforum.org

	TETRA TETRA 2 (TEDS)	Tetrapol	Project 25 APCO-25	SIGFOX	LoRaWAN	WLAN/Wi-Fi IEEE 802.11a, b, g, n, p, ac, ax	WLAN/Wi-Fi HaLow™ IEEE 802.11ah	WLAN/Wi-Fi IEEE 802.11ad, aj*, ay*	Bluetooth®	LR-WPAN ZigBee/Thread/ 6LoWPAN IEEE 802.15.4	NFC, RFID ISO/IEC 18000, NFC Analog Specification	DECT, ULE
Modulation type	QPSK, 8PSK, 16QAM, 64QAM (FL, Rev. B) 8PSK, QPSK, 8PSK (RL)	GMSK	C4FM, OQPSK	GFSK (DL) DBPSK (UL)	LoRa™, GFSK (Europe) LoRa™ (US)	8PSK, ASK, OQPSK, 64QAM (11a, g, n, p, ac, ax) 256QAM (11ac, ax) 1024QAM (11ax) DBPSK, DQPSK, CCK, PBCC (11b, g)	8PSK, QPSK, 16QAM, 64QAM, 256QAM	SQPSK, QPSK, 16QAM, 64QAM (OFDM), π/2-BPSK, π/2-QPSK, π/2-16QAM (SC) π/2-64QAM (SC, 11aj) 8-PSK (SC, 11ay)	GFSK (BR,LE) GFSK (EDR, Header) π/4-DQPSK, 8DPSK (EDR, Payload)	FHSS	DSSS, CSMA/CA GFSK, BPM, DQPSK, MPSK, MSK, MR-FSK OQPSK (ZigBee 3.0, Thread, 6LoWPAN)
Transmission method/ multiple access	TDMA (FL) CDMA (RL)	CDMA	OFDM (256) (16-2012 only) SOFDMA (128, 256, 512, 1024, 2048)	TDMA	FDMA	FDMA (Phase 1) TDMA (Phase 2)	UNB	CSS	OFDM, CSMA/CA DL MU-MIMO (11ac, ax) UL MU-MIMO (11ax) OFDMA (11ax)	OFDM, CSMA/CA, CCA	OFDM, CSMA/CA DL MU-MIMO (11ay)	DSSS, PSSS, CSMA/CA, UWB, CSS, OFDM; DSSS, CSMA/CA (ZigBee 3.0, Thread, 6LoWPAN)
Duplex	FDD	FDD	FDD, TDD	FDD	FDD	FDD	TDD/FDD	TDD/FDD	TDD	TDD	TDD	TDD
Channel bandwidth	1.25 MHz (RL, Rev. A) 1.25 MHz x N (Rev. B) (N = number of channels, max. 15)	1.25 MHz	12.5 kHz, 6.25 kHz (Phase 2)	100 Hz (UL) 600 Hz (DL, Europe) 600 Hz (UL, North America)	125 kHz, 250 kHz, 500 kHz	10 MHz (11p) 20 MHz (11a, g, n, ac, ax) 22 MHz (11b) 40 MHz (11n, ac, ax) 80 MHz, 160 MHz (11ac, ax)	1 MHz, 2 MHz (mandatory) 4 MHz, 8 MHz, 16 MHz (optional)	540 MHz (11aj) 1.08 GHz (11aj) 2.16 GHz (11ad,ay) 4.32 GHz (11ay) 8.64 GHz (11ay)	Channel spacing: 1 MHz (BR, EDR) 2 MHz (LE)	600 kHz, 1 MHz, 2 MHz, 499.2 MHz, 1081.6 MHz, 1331.2 MHz, 1354.97 MHz dependent on standard; 2 MHz (ZigBee 3.0, Thread, 6LoWPAN)	typ. 200 kHz/500 kHz	1.728 MHz
Peak data rate	2.4 Mbit/s (FL, Rel. 0) 153 kbit/s (RL, Rel. 0) 3.1 Mbit/s (FL, Rev. A) 1.8 Mbit/s (RL, Rev. A) 4.9 Mbit/s x N (FL, Rev. B) 1.8 Mbit/s x N (RL, Rev. B) (N = number of channels, max. 15)	153.6 kbit/s (Rel. 0) 307.7 kbit/s (Rev. E)	9.4 kbit/s



Wireless Communications Standards

Poster

Service that adds value

- Worldwide
- Local and personalized
- Customized and flexible
- Uncompromising quality
- Long-term dependability

About Rohde&Schwarz

The Rohde&Schwarz electronics group is a leading supplier of solutions in the fields of test and measurement, broadcasting, secure communications, and radiomonitoring and radiolocation. Founded more than 80 years ago, this independent global company has an extensive sales network and is present in more than 70 countries.
The company is headquartered in Munich, Germany.

Sustainable product design

- Environmental compatibility and eco-footprint
- Energy efficiency and low emissions
- Longevity and optimized total cost of ownership

Certified Quality Management ISO 9001

Certified Environmental Management ISO 14001

Rohde&Schwarz GmbH&Co. KG
www.rohde-schwarz.com

Regional contact

- Europe, Africa, Middle East | +49 89 4129 12345
  customersupport@rohde-schwarz.com
- North America | 1 888 TEST RSA (1 888 837 87 72)
  customer.support@rsa.rohde-schwarz.com
- Latin America | +1 410 910 79 88
  customersupport.la@rohde-schwarz.com
- Asia Pacific | +65 65 13 04 88
  customersupport.asia@rohde-schwarz.com
- China | +86 800 810 82 28 | +86 400 650 58 96
  customersupport.china@rohde-schwarz.com

R&S® is a registered trademark of Rohde&Schwarz GmbH&Co. KG
Trade names are trademarks of the owners
PD 0758.1441.82 | Version 17.00 | July 2018 (as)
Wireless Communication Standards
Data without tolerance limits is not binding | Subject to change
© 2008 - 2018 Rohde&Schwarz GmbH&Co. KG | 81671 Munich, Germany

3574916-00
0706.1441.82 17.00 PDP 1 en